

# ATEX II 3 GD Certificate

## RELC07ATEX1005X

We, Relcom, hereby declare that the following equipment complies with Directive 94/9/EC (ATEX):

FPS-I	Redundant Power System with Terminator
FPS-2	Redundant Power System
FPS-RCT	Redundant Base with Terminator
FPS-RC	Redundant Base
FPS-DT	Dual Power System with Terminator
FPS-D	Dual Power System
FPS-DCT	Dual Base with Terminator
FPS-DC	Dual Base
FPS-IPM	Isolated Power Module

Manufactured by:

Relcom, Inc. 2221 Yew Street, Forest Grove, OR, 97116, USA  
Measurement Technology Limited, Power Court, Luton Beds. LU1 3JJ. UK  
MTL Instruments Pvt. Ltd., No 3 Old Mahabalipuram Rd., Sholinganallur, Chennai, 600119, India

Authorized Representative in the EU:

Measurement Technology Limited, Power Court, Luton Beds. LU1 3JJ. UK

This equipment fulfils all the requirements for Group II, Category 3 G equipment in accordance with Directive 94/9/EC. The equipment comply with:

IEC 60079-0:2004 "Electrical apparatus for potentially explosive atmospheres - General requirements"  
IEC 60079-15:2005 "Electrical apparatus for potentially explosive atmospheres – Construction, test and marking of type of Protection 'n' electrical apparatus"

The design is documented in the Relcom Technical File No. 500-464

The safety marking, **Ex nA IIC T4**, of the apparatus is specified in the Technical File (Document No. 500-464) and includes the distinctive community marks:



The maximum output parameters are: 30V, 1.5A.

Manufacture is internally controlled by a Quality Management System modeled after ISO 9001:2000 and EN13980:2002.

The apparatus is designed to be installed and used in accordance with IEC 60079-14:2003.

The ambient operating temperature range is -40°C to +60°C.

Apparatus meets the ATEX Directive requirements for personnel protection by complying with the LVD Directive 2006/95/EC. The personnel safety standards of EN61010-1 are also met by the apparatus.

**Special Conditions of safe use:** The Apparatus must be installed in an enclosure or an environment that ensures at least IP54 protection. When mounted in Zone 22 (dust) hazardous areas, the enclosure in which the apparatus is mounted should meet the requirements of IEC 61242.

Senior Fieldbus Engineer

Rev: A - 10/08/07

M. Graube  
President



**Relcom Inc.**

INDUSTRIAL LAN | WIRING COMPONENTS AND TESTERS